


## OPERATION

The 657-8-4000 timer has two (2) user selectable modes of operation; ON Delay and Interval. In either operation mode the user can select from 2 output contact configurations; 2 timed contacts or 1 timed contact and 1 instantaneous contact. Selection of the operating mode and contact output configuration choice provides the user with timing control versatility.

## WIRING



## SPECIFICATIONS

TIMING RANGES	0.1—12.7 SEC
	0.1—12.7 MIN
	0.1—12.7 HR
	1.0—127 SEC
	1.0—127 MIN
TIMING MODES—SELECTABLE	ON Delay W/2 Timed Contacts
	ON Delay W/1 Timed and 1 Instantaneous Contact.
	Interval Timer 2 Timed Contacts
	Interval Timer 1 Timed Contact & 1 Instantaneous Contact
TIME SETTING METHOD	DIP Switches Located On Top
RESET TIMES	50 mSEC Max.
OPERATING POWER	Universal, 85-240 VAC or VDC
REPEAT ACCURACY	±0.002% of Timed Setting
RELAY OUTPUTS	2 Each, SPDT Form C 10A @ 120 VAC, 5A @ 240 VAC / 30 VDC
POWER CONSUMPTION	30mA Max.
TEMPERATURE RATING	Operate 32° - 122°F (0 - 50°C)
TERMINATION—MOUNTING	8 Pin, Plug-In Socket
LED INDICATORS	Green LED ON Steady when powered but not timing. Flashing when timing
	Red LED ON when relay outputs are on
WEIGHT	4 oz. (approximately)



CALUS

Universal 2-Mode Timer

- 2 SPDT 10A @ 120 VAC Relays
- Universal Input Power 85-240 VAC/DC
- LED Indicators—Show Operating Status and Relay Contact Status
- Six (6) Time Bases From 0.1 Second to 127 Hours
- Convenient Top Mounted Time Setting Switches
- Extremely Cost Effective

## ORDERING INFORMATION

MODEL NUMBER	Description
657-8-4000	Universal 2 Mode timer