


ATC T45 Series steady ON lights are less than two (2) inches in diameter and ideal for applications where compact cost effective indicating lights are required. They are available in base or pole mounting, one through five light models, non-flashing only.

DIMENSIONS (MILLIMETERS)

NOTE: The dimensions shown are for T45 BASE MOUNT models. For pole mounted models add 198mm to the overall height.



45mm Diameter Steady Indicating Lights



ORDERING INFORMATION

MODEL NUMBER	LAMP DIAMETER	NO. OF LIGHTS	LIGHT MODE	MOUNTING
T45BS-110-1	45mm	1	Steady	Base
T45BS-110-2	45mm	2	Steady	Base
T45BS-110-3	45mm	3	Steady	Base
T45BS-110-4	45mm	4	Steady	Base
T45BS-110-5	45mm	5	Steady	Base
T45PS-110-1	45mm	1	Steady	Pole
T45PS-110-2	45mm	2	Steady	Pole
T45PS-110-3	45mm	3	Steady	Pole
T45PS-110-4	45mm	4	Steady	Pole
T45PS-110-5	45mm	5	Steady	Pole

*For 24VDC Models: Substitute 24DC for 110 in Model Number.

For replacement bulbs, see chart below.

- Steady Illuminating Lights
- One Through Five Light Models
- Pole or Base Mounting
- Replaceable Bulbs

SPECIFICATIONS

OPERATING VOLTAGE	110 VAC, 50/60 Hz.
BULB RATINGS	24 VDC
RECOMMENDED SWITCH RATING	5 Watt
TERMINATION	1A
MOUNTING	Wire Leads
WEIGHT	Pole With Base or Base
	0.7 lbs. to 1.7 lbs.

REPLACEMENT BULBS

LIGHTS	12VDC	24VDC	24VAC	110VAC	220VAC
HYT Models	ST-BLB 12-B	ST-BLB 24-B	ST-BLB 24-B	ST-BLB 110-B5	ST-BLB 220-B5
T45 Models	T45 BULB-12-5W	T45 BULB-24-5W	T45 BULB 24-5W	T45 BULB-110-5W	T45 BULB-240-5W
T56 Models	N/A	T56 BULB-24-8W	N/A	T56 BULB-110-8W	N/A
TF Models	ST-BLB 12-B	ST-BLB 24-B	N/A	ST-BLB 12-B	ST-BLB 12-B
TP Models	ST-BLB 12-B	ST-BLB 24-B	N/A	ST-BLB 12-B	ST-BLB 12-B
TR Models	ST-BLB 12-B	ST-BLB 24-B	N/A	ST-BLB 12-B	ST-BLB 12-B
TR125 Models	N/A	N/A	N/A	TR125 BULB-110	N/A
TX Models	ST-BLB 12-B	ST-BLB 24-B	N/A	ST-BLB 12-B	ST-BLB 12-B