

ICI IP Security



System Features

- No shutter
- Instantaneous start-up
- H.264 video output
- Super low power consumption
- Athermalized lens
- Mobile phone ready (optional)
- WiFi ready (optional)



Specifications

| | |
|----------------------------------|--|
| Detector type | 384 X 288 UFPA |
| FOV | 28.6° X 21.45° - 18mm 15.5° X 11.5° - 35mm |
| Spatial Resolution | 0.7 mrad |
| Thermal sensitivity | < 80mk @ 300k |
| Frame rate | 50Hz |
| Image Mode | Auto adjust White Hot |
| Measurement Range | -20°C - 60°C |
| Spectral range | 8-14 microns |
| Boot Time | < 3s |
| Noise Reduction | Digital Filter |
| Shutter Speed | No Shutter |
| Focus | Fixed Focus, Electrical Focus (optional) |
| Power Supply | DC: +12V |
| Storage Temperature Range | -50°C to 65°C |
| Encapsulation | IP67 |
| Cable | Waterproof RF45 cable with 1m power cable |
| Network Protocol | ONVIF, RTSP, FTP, PPPOE, DHCP, DDNS, NTP, UPnP |
| Default IP Address | 192.168.1.10 |
| 3G / WiFi | Optional |
| Alarm | 2 channel switching value input 1 channel switching value output |
| Mobile Phone | iPhone, Windows Mobile, Black Berry, Symbian, Android |
| SD Card | 35G Maximum |
| Subtitle Overlying | Yes |
| Video Process | H.264 video format, support dual stream, AVI format, support 0.1M - 6Mbps stream, Frame rate 1 - 30 frames. |
| Video Output | Main Stream: 704*576, 352*288 Sub Stream: 352*288 |
| Weight | 500g with bracket |
| Dimension | 183mmX120mmX110mm with bracket |